



9500 series

Industrial Mobile Computer

Designed to fit your world, the 9500 series gives you the right data capture tools at the right time, so you can make smarter decision for your business.

Powerful and rugged, the 9500 is versatile and efficient partner for any worker, in any warehouse and manufacturing environment. With the 9500's Windows CE5.0 operating support, RFID and imager or laser barcode reading capability, and seamless wireless communication to your corporate information, work is safer, easier and much more productive.

SPECIFICATIONS

9500 series

Industrial Mobile Computer



ACCESSORIES



Charging and Communication Cradle
USB client / USB host / Ethernet



4-Slot Battery Charger



Belt Holster



Protective Cover



Pistol Grip

	9500	9570	
Performance	Operating system	Microsoft® Windows® CE 5.0 Professional	
	CPU	XScale™ PXA270 @ 520 MHz	
	Memory	128MB Flash ROM 128MB SDRAM	
	Expansion	SD card slot / CF type 2 slot	
	Operating power	Removable, rechargeable 3.7V 4000 mAh Li-ion battery	
		Adapter: AC 110V / 220V input DC 6V 3.3 A output via cradle	
	Working hours ¹	20 hours batch mode 13 hours WLAN mode	
	Backup power	3.7V 110 mAh Lithium battery	
Data sustained 6 hours minimum			
Alerts	Volume adjustable speaker / Programmable vibrator / LED signals		
Wireless communication	WLAN 300 m / 984 ft. line of sight ²	-	IEEE 802.11b/g
	WWAN	BT Class 2 compliance	
Data capture	Barcode scanning	Linear imager / Laser / Long-range laser / Extra-long-range laser / 2D imager	
	RFID reader/writer	Frequency: 13.56 MHz Supported tags ISO 14443A, ISO 14443B, ISO 15693, ICODE	
Physical characteristics	Display	3.5" Color QVGA, TFT transfective, touchscreen, LED backlight	
	Keypad	27 keys LED backlight	
	LED	Tri-color: green, red, blue	
	Size (L x W x H) Weight	230 x 91 x 63 mm / 9.1 x 3.6 x 2.5 in. 600 g / 21.2 oz. configuration dependent	
	User environment	Operating temperature	-10° to 50°C / 14° to 122°F
Storage temperature		-20° to 60°C / -4° to 140°F	
Humidity		5% to 95% non-condensing	
Impact resistance		Multiple 1.5 m / 5 ft. drops onto concrete, 5 drops on each side / IP64	
Electrostatic discharge		±8 kV direct electrostatic discharge	
EMC regulation		CE, C-Tick, FCC, RSS-210, TELEC, SRMC, RRL, BSMI, NCC	
Development support	CipherLab C++ DLL, 9500 SDK to support Microsoft® Visual Studio 2005		
Application software	Application Manager, FORGE Application Generator, MIRROR Browser and Terminal Emulator, MCL, Wavelink®, SOTI MobiControl		
Cradles	USB client / USB host / Ethernet		
Accessories	4-slot battery charger, belt holster, protective cover, pistol grip		
Warranty	1 year		

¹ Based on one standard laser scan per five seconds with backlight on. ² Effective coverage depends on user environment and equipment deployment. It is highly recommended to conduct a site survey before actual deployment.

©2010 CipherLab Co., Inc. All specifications are subject to change without notice. All rights reserved. All brand, product and service names, and trademarks are the property of their registered owners.



HEADQUARTERS
CipherLab Co., Ltd.
12F, 333 Dunhua S. Rd., Sec. 2
Taipei, Taiwan 10669
Tel +886 2 8647 1166
Fax +886 2 8732 3300
www.cipherlab.com

CipherLab China
Suite 1305, 1065A, Jaojiabang Rd.
Xuhui District, Shanghai,
China 200030
Tel +86 21 3368 0288
Fax +86 21 3368 0286

CipherLab USA
2552 Summit Avenue
Plano, Texas USA 75074
Tel +1 469 241 9779
Toll Free 888 300 9779
Fax +1 469 241 0697

CipherLab Central Europe
Willicher Damm 143-145
41066 Mönchengladbach
Germany
Tel +49 2161 56230 0
Fax +49 2161 56230 22