


KS-6715 Series

www.posiflex.com

Specification	KS-6715G-I	KS-6715G
Processor	VIA Nano 1.6 GHz / 1M cache CPU	
System Memory	DDR3 1066 MHz, SO-DIMM x 1, max 4GB, default 1 GB	
Storage Device	2.5" SATA HDD or SSD (Optional)	
Power Supply	12V DC power adaptor, 60W (Optional 80W when equipping with 2nd 15" LCD LM-8015 / 8025 / 8035 / 8045 / 8055 / TM-8045)	
Audio	Buzzer	
OS support	Win 7 / Win XP Pro / POSReady 7 / POSReady 2009 / DOS / Linux	
Display		
LCD	15" TFT LCD, 1024 x 768 resolution	
Touch Function	IR touch, USB interface	Resistive, 5-wire, USB interface
Brightness Control	By push button	
Tilt Adjustment	From 15° to 70°	
Connectivity		
LAN Port	10 / 100 / 1000 Mb	
Parallel Port	Optional	
Serial Port	DB9 x 4, with 5V / 12V support on COM1 / COM2 / COM3 / COM4	
Standard USB Port	6 (4 ports on the I/O plate, 2 port on the left side)	
Proprietary USB Port	1 for side mounted option	
VGA Port	D-SUB 15 Pins, with 12V power for Posiflex LCD monitor	
CR Port	1, control 2 CR	
Physical Dimension		
Dimension (W x D x H in mm)	378 x 309 x 360	
Weight (N. W. in kg)	6.9	
Environment		
Operation Condition	0°C - 40°C, 20%RH - 90%RH (Equipped with HDD) ; 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)	
Storage Condition	(-20°C) - 70°C, 10%RH - 90%RH	
Options		
SSD	8 GB minimum	
WiFi	802.11 b / g, USB interface	
2nd LCD Display	12" LM-6101B, 15" LM-6501B / LM-8015 / 8025 / 8035 / 8045 / 8055 / TM-8045	
PD-306 / PD-306U	2 x 20 LCD, default 200 mm pole	
PD-310 / PD-310U	2 x 20 LCD, rear top mount	
PD-2602 / PD-2602U	2 x 20 VFD, default 200 mm pole	
PD-2604 / PD-2604U	2 x 20 VFD, rear top mount	
PD-76x2	240 x 64 dot Graphics LCD, 200 mm pole	
PD-305	2 x 20 LCD, rear top mount	
MSR	See Security Device	
Security Device	SD-400W/SD-400T : 2 or 3 tracks and JIS-II (Optional) and/or fingerprint sensor (Optional), SD-600 : iBotton or 2 or 3 tracks and JIS-II (Optional), SD-800 : 2 or 3 tracks and JIS-II (Optional) or RFID (Optional) or WiFi (Optional)	
KP-300W	36 Key plus lock keypad with MSR (Optional) or card reader (Optional)	
Certifications		

Design and Manufacturing In Taiwan by Posiflex Technology Inc.

2011 Preliminary Version

** The product information and specifications are subject to change without prior notice.

POSIFLEX
Your Success is Our Vision

Posiflex Technology, Inc.
Headquarters
No.6, Wuquan Rd., Wugu Dist., New Taipei City
248, Taiwan (R.O.C.)
Tel: +886 2 2299-1599 Fax: +886 2 2299-1819
sales@posiflex.com.tw www.posiflex.com

Authorized Distributor / Reseller