

SPECIFICATIONS - MP200 7- PIN



Paper Feed Method	Mechanical
Paper Width	3" (76mm)
Copy Capability	1 + 2
Paper Thickness (Single Multi)	0.07 - 0.10mm / 0.2mm
Paper End Sensor	*
Ribbon	*
RC200P Purple RC200B Black	
Operating Temperatures	0 ± to 50 ± C

INDIVIDUAL SPECIFICATIONS -



Individual Specifications	No. of Cols	Friction / Sprocket	Speed lines / sec.	Red/Black Print RC200BR	Supply Voltage	MCBF Lines (Millions)	Print Head Characters (Millions)	Control Board	Dimensions WxDxH(mm)
MP212FP-12-A	42	F	2.5 lps	-	12v	2.5	75	BD200FC-12-A	132 x 96 x 48.3
MP212FP-24-A	42	F	2.5 lps	-	24v	2.5	75	BD200FC-24-A	132 x 96 x 48.3
MP212FP-24G-A	42	F	3.1 lps	-	24v	2	50	-	132 x 96 x 48.3
MP216FP-12-A	42	F	2.5 lps	-	12v	2.5	75	BD200FC-12-A	132 x 96 x 48.3
MP216-24-A With cutter	42	F	2.5 lps	-	24v	2.5	75	BD200FC-24-A	142 x 108 x 78.47
MP246FP-24-A	42	F	2.5 lps	*	24v	2.5	75	BD200FC-24-A	142 x 108 x 78.47
MP221SP-24G-A	28	S	4.39 lps	-	24v	2	50	-	132 x 102 x 58.44
MP221SGP-24G-A	28	S	4.39 lps	-	24v	-	50	-	132 x 102 x 58.44
MP221SHP-24-A	28	S	4.2 lps	-	24v	2	50	-	132 x 102 x 58.44