


3-inch Pinhole printer

NP-366



Features

- High speed (220mm/sec) print.
- Drop-in type, easy paper loading.
- Presenter NPT-305 is available.

Application

- Information Kiosk
- Fuel-Pump
- Parking lot system
- Self check-out terminal

Dimensional drawing

Specifications

Model	NP-366
Print method	Line thermal dot
Paper width / Print width	80mm / 72mm
Print speed	Max. 220mm/sec.
Resolution	8dots/mm
Character size (dot x dot)	FontA(12x24):1.50x3.00mm,FontB(9x17):1.13x2.13mm
Character types	ANK, Japanese, Extend graphic character set, International, Polish, Russian, Scandinavian, Turkish
Barcode	UPC-A, UPC-E, JAN13(EAN), JAN8(EAN), CODE39, ITF, CODA BAR, CODE128, QRcode
Line feed pitch	0.125mm
Interface	Serial(RS232C), USB(V2.0 Full Speed) *Factory setting
Input buffer	Approx. 10kb
Operating voltage	Type I: DC5V±5%, DC24V±5%, Type II: DC24V±5%
External Dimensions	129(W) x 107(D) x 163(H) mm
Weight	Approx. 1300g
Paper type	Thermal paper (80mm in diameter)
Operating temperature	5 ~ 45°C
Storage temperature	-10 ~ 50°C
Reliability (head)	More than 100 million pulses, More than 100Km wear distance
Auto cutter	500,000cuts, Full cut or Partial cut *Factory setting
Safety regulation	-

3-inch

Pin hole

Auto Cutter

DED
LIMITED

Mill Road, Lydd, Kent. TN29 9EJ

Tel: 01797 320636



Fax: 01797 320273

Email: sales@ded.co.uk

Web: www.ded.co.uk

3-inch Pinhole printer

NP-366Slim



Features

- High Speed 220 mm/sec print
- Drop-in type, easy paper loading
- Presenter NPT-305 is available

Application

- Fuel-Pump
- Information Kiosk
- Parking lot system
- ATM / CD

Dimensional drawing

3-inch

Pin hole

Auto Cutter

Specifications

Model	NP-366Slim
Print method	Line thermal dot
Paper width / Print width	80mm / 72mm
Print speed	Max. 220mm/sec.
Resolution	8dots/mm
Character size (dot x dot)	FontA(12x24):1.50x3.00mm, FontB(9x17):1.13x2.13mm, Kanji(24 x 24) : 3.00x3.00mm
Character types	ANK, Japanese, Extend graphic character set, International, Korean, Chinese (GB18030-2000), Greek, Polish, Russian, Scandinavian, Turkish
Barcode	UPC-A, UPC-E, JAN13(EAN), JAN8(EAN), CODE39, ITF, CODA BAR, CODE128, QRcode
Line feed pitch	0.125mm
Interface	Serial(RS232C), USB(V2.0 Full Speed) *Factory setting
Input buffer	Approx. 10kb
Operating voltage	Type I: DC5V±5%, DC24V±5%, Type II: DC24V±5%
External Dimensions	127.2(W) x 97.8(D) x 131.3(H) mm
Weight	Approx. 1000g
Paper type	Thermal paper (50mm in diameter)
Operating temperature	5 ~ 45°C
Storage temperature	-10 ~ 60°C
Reliability (head)	More than 100 million pulses , More than 100Km wear distance
Auto cutter	500,000cuts, Full cut or Partial cut *Factory setting
Safety regulation	-

DED
LIMITED

Mill Road, Lydd, Kent. TN29 9EJ

Tel: 01797 320636

Fax: 01797 320273

Email: sales@ded.co.uk

Web: www.ded.co.uk