

NEW**SM-S400****SM-T300****SM-T300DB**
Bluetooth and
Serial without
Magnetic Stripe
Reader**SM-T301DB**
Bluetooth with MSR**SM-T301DW**
WiFi version with MSR**SM-S200****SM-S300**

Mobile Printers

Fast, lightweight and small. Star's new range of wireless mobile printers provide easy-to-use printing solutions for delivery receipts; field service estimates, reports, parts lists; inventory management schedules; mobile point-of-sale receipting and sales orders to name just a few applications.

SM-S200

2"

58mm Mobile Printer with Blue Light LCD Display

Sophisticated pocket size printer capable of producing high quality output at a fast 80mm/sec. with Bluetooth and Serial connections as well as a cover open sensor and power save facility



Blue Light Display



Easy Paper Loading

SM-T300

3"

80mm rugged Mobile Printer with LCD display & WiFi version

Ultra rugged with IP54 dust / splash proof certification. Available with or without the magnetic stripe reader with Bluetooth and WiFi versions



LCD Display



Rugged Design

Options available



Carrying Case for SM-S200



Car Charger



1-Bay Charger



Shoulder Strap for SM-T300

SM-S300

3"

80mm Mobile Printer

Pocket size 80mm workhorse with an extended battery life of 10 hours with Bluetooth for wireless communication and Serial for printer settings and set-up



Magnetic Stripe Reader with Serial & Bluetooth



Easy Paper Loading

SM-S400

4"

112mm Mobile Printer

Wide, 104mm output for data filled service reports, delivery notes or law enforcement parking or motoring tickets in a compact case



Wide 112mm Paper Width



Easy Paper Loading



4-Bay Battery Charger

DED
LIMITEDDED Limited
Harden Road, Lydd, Kent
TN29 9LX, EnglandTel: +44 (0)1797 320636
Email: sales@ded.co.uk
www.ded.co.ukwww.Star-EMEA.com

SM-S200 Printer Specifications

Print Method	Direct Line Thermal Printing
Print Speed	80mm/sec
Print Width	48mm / 2"
Print Resolution	203 dpi
Dimensions	80.5 (W) x 113.5 (D) x 46 (H) mm
Weight	232g (with battery)
Battery Duration	6 hour printing (5 minute intervals)
AC Adaptor	4 hours full charge time
Power Voltage	7.4V
Paper:	
Media	Thermal Paper
Loading Method	"Drop-In & Print"
Width	58mm
Thickness / Weight	0.06 - 0.07mm
Roll Diameter	39mm
Interface	Bluetooth (2.1), Serial
Print Head Reliability	50km
Barcode	Code39/93/128, JAN/EAN8, JAN/EAN13, EAN128, 12/5, KAN, UPC, CODABAR, PDF417, QR Code, DATA Matrix
Drop Test	1m
Operating System Support	Windows® 7 32/64 Bit, Vista 32/64 Bit, XP 32 Bit, Server 2008, 32/64 Bit, CE, StarIO SDK
Magnetic Stripe Reader	Standard 1&2 Track (2&3 optional)
Auto Power Down Mode	1-5 minutes configurable
Characters per line	42
Character Support	ANK, Simplified/Traditional Chinese, Arabic, Cyrillic, Russian, Turkish, Greek, Japanese, Persian, Latin 9 and others (upon request)
Included	AC Charger, Battery Pack, Serial Cable, Sample Roll, Setup Sheet
Options	4 Unit Battery Charger, Car Charger, Leather Case, Extra Battery Charger, Extra Battery Pack



SM-T300 Printer Specifications

Print Method	Direct Line Thermal Printing
Print Speed	75mm/sec
Print Width	72mm / 3"
Print Resolution	203 dpi
Dimensions	120 (W) x 130.5 (D) x 58.4 (H) mm
Weight	422g (with battery)
Battery Duration	8 hour printing (5 minute intervals)
AC Adaptor	4 hours full charge time
Power Voltage	7.4V
Paper:	
Media	Thermal Paper
Loading Method	"Drop-In & Print"
Width	80mm
Thickness / Weight	0.06 - 0.07mm
Roll Diameter	50mm
Interface	Bluetooth & Serial / WIFI versions
Print Head Reliability	50km
Barcode	Code39/93/128, JAN/EAN8, JAN/EAN13, EAN128, 12/5, KAN, UPC, CODABAR, PDF417, QR Code, DATA Matrix
Drop Test	1m
Operating System Support	Windows® 7 32/64 Bit, Vista 32/64 Bit, XP 32 Bit, Server 2008, 32/64 Bit, CE, StarIO SDK
Magnetic Stripe Reader	Standard 1&2 Track (2&3 optional)
Auto Power Down Mode	1-5 minutes configurable
Characters per line	64
Character Support	ANK, Simplified/Traditional Chinese, Arabic, Cyrillic, Russian, Turkish, Greek, Japanese, Persian, Latin 9 and others (upon request)
Included	AC Charger, Battery Pack, Serial Cable, Belt Clip, Sample Roll, Setup Sheet, IP54 Certified
Options	4 Unit Battery Charger, Car Charger, Shoulder Strap, Extra Battery Charger, Extra Battery Pack



SM-S300 Printer Specifications

Print Method	Direct Line Thermal Printing
Print Speed	65mm/sec
Print Width	72mm / 3"
Print Resolution	203 dpi
Dimensions	107.4 (W) x 88.5 (D) x 45 (H) mm
Weight	269g (with battery)
Battery Duration	10 hour printing (5 minute intervals)
AC Adaptor	4 hours full charge time
Power Voltage	7.4V
Paper:	
Media	Thermal Paper
Loading Method	"Drop-In & Print"
Width	80mm
Thickness / Weight	0.06 - 0.07mm
Roll Diameter	38mm
Interface	Bluetooth (2.1), Serial
Print Head Reliability	50km
Barcode	Code39/93/128, JAN/EAN8, JAN/EAN13, EAN128, 12/5, KAN, UPC, CODABAR, PDF417, QR Code, DATA Matrix
Drop Test	0.9m
Operating System Support	Windows® 7 32/64 Bit, Vista 32/64 Bit, XP 32 Bit, Server 2008, 32/64 Bit, CE, StarIO SDK
Magnetic Stripe Reader	Standard 1&2 Track (2&3 optional)
Auto Power Down Mode	1-5 minutes configurable
Characters per line	64
Character Support	ANK, Simplified/Traditional Chinese, Arabic, Cyrillic, Russian, Turkish, Greek, Japanese, Persian, Latin 9 and others (upon request)
Included	AC Charger, Battery Pack, Serial Cable, Sample Roll, Setup Sheet
Options	4 Unit Battery Charger, Car Charger, Extra Battery Charger, Extra Battery Pack



SM-S400 Printer Specifications

Print Method	Direct Line Thermal Printing
Print Speed	50mm/sec
Print Width	104mm / 4"
Print Resolution	203 dpi
Dimensions	138.4 (W) x 88.5 (D) x 45.7 (H) mm
Weight	321g (with battery)
Battery Duration	11 hour printing (5 minute intervals)
AC Adaptor	4 hours full charge time
Power Voltage	7.4V
Paper:	
Media	Thermal Paper
Loading Method	"Drop-In & Print"
Width	112mm
Thickness / Weight	0.06 - 0.07mm
Roll Diameter	38mm
Interface	Bluetooth (2.1), Serial
Print Head Reliability	50km
Barcode	Code39/93/128, JAN/EAN8, JAN/EAN13, EAN128, 12/5, KAN, UPC, CODABAR, PDF417, QR Code, DATA Matrix
Drop Test	0.9m
Operating System Support	Windows® 7 32/64 Bit, Vista 32/64 Bit, XP 32 Bit, Server 2008, 32/64 Bit, CE, StarIO SDK
Magnetic Stripe Reader	Standard 1&2 Track (2&3 optional)
Auto Power Down Mode	1-5 minutes configurable
Characters per line	92
Character Support	ANK, Simplified/Traditional Chinese, Arabic, Cyrillic, Russian, Turkish, Greek, Japanese, Persian, Latin 9 and others (upon request)
Included	AC Charger, Battery Pack, Serial Cable, Sample Roll, Setup Sheet
Options	4 Unit Battery Charger, Car Charger, Extra Battery Charger, Extra Battery Pack

