

SPECIFICATIONS - MP300 Series 9-pin



Common Features	MP300/320 MP330
9-Pin	*
Paper Feed Method	Stepping Motor
Copy Capability	1 + 2
Paper Thickness (Single / Multi-part)	0.07mm-0.10mm / 0.2mm
Print Head Characters (Millions)	100
Operating Temperatures	5° to +50°c
Graphics Capability	*
Ribbon RC300P Purple / RC300B Black	*
Supply Voltage	24

INDIVIDUAL SPECIFICATIONS



Individual Specifications	No. of Cols	Friction / Sprocket	Speed lines / sec.	Cutter	MCBF Lines (Millions)	Paper Width	Control Board**	Dimensions WxDxH(mm)
MP312F-24-A	40	F	3.2 lps	-	5	57.5mm/76mm/ 82.5mm	BD300 FC/FD-24	136.9 x 187.9 x 65.1
MP317FV-24-AC*	40	F	5.5 lps	-	5	3.25" (82.5mm)	BD317 FC/FD-24	136.9 x 187.9 x 65.1
MP342FX-24-A	40	F	3.2 lps	Partial	5	57.5mm/76mm/ 82.5mm	BD300 FC/FD-24	136.9 x 187.9 x 84.6
MP342FX-24-L	40	F	3.2 lps	Full	5	57.5mm/76mm/ 82.5mm	BD300 FC/FD-24	136.9 x 187.9 x 84.6
MP347FXV-24-AC*	40	F	5.5 lps	Partial	5	3.25" (82.5mm)	BD347 FC/FD-24	136.9 x 187.9 x 84.6
MP382FW-24-L With Presenter	40	F	3.2 lps	Full	5	3.25" (82.5mm)	BD382 FC/FD-24	136.9 x 187.9 x 143.13